

# ***Yueng-Clings***

## **APPLICATION INSTRUCTIONS FOR YOUR YUENG-CLING**

### Requirements:

1. 2 people
2. A dry, smooth, and flat wall. (painted drywall or other painted smooth surface, glass or metal) Textured walls will not work. Wall paper is ok but it must be clean and smooth. Some wall papers have coatings that will prevent your Yueng - Cling from adhering properly.
3. Tape measure
4. Included squeegee
5. Patience

- A. Allow the Yueng - Cling to lie flat for at least 45 minutes to.
- B. Place Yueng - Cling on wall surface with backing sheet still attached and measure out the correct desired position.
- C. Using a pencil lightly mark the position on the wall just inside the edge.
- D. Remove Yueng - Cling from wall and then remove the backing sheet from the top edge of Yueng - Cling.  
Pull away about half of the backing sheet starting at the top.
- E. Lightly position the top section of Yueng - Cling against the wall following your previously marked position.  
Once Yueng - Cling is in place, use the included squeegee to press and anchor the top edge to the wall.
- F. Squeegee the Yueng - Cling to the wall being careful to overlap your passes and remove all air. Work down from the top. The backing sheet still attached to the bottom of the graphic will help to keep the Yueng - Cling angled away from the wall. Just remove more backing sheet as you work your way down with the squeegee until fully applied.
- G. Re-squeegee entire graphic placing particular emphasis on the outer edges.

Note.. Freshly painted walls should be allowed to dry for a full month before applying your Yueng - Cling.  
This product is not intended for outdoor or vehicle surfaces. It is for indoor use only.